# This Page Is Inserted by IFW Operations and is not a part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.

This Page Blank (uspto)

#### **PCT**

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISH	HED	JNDER THE PATENT COOPERATION TREATY (PCT)
(51) International Patent Classification <sup>6</sup> :		(11) International Publication Number: WO 97/1201
C11D 1/65, 1/86, 17/00	A1	(43) International Publication Date: 3 April 1997 (03.04.97
(21) International Application Number: PCT/US9 (22) International Filing Date: 27 September 1996 (2)		(AT. BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU
(30) Priority Data: 60/004,548 29 September 1995 (29.09.95)  (71) Applicant (for all designated States except US): THE TER & GAMBLE COMPANY [US/US]; One Pri Gamble Plaza, Cincinnati, OH 45202 (US).	PRO	
<ul> <li>(72) Inventors; and</li> <li>(75) Inventors/Applicants (for US only): ZHEN, Yueqian (6) 9618 Friar Tuck Drive, West Chester, OH 4506 De BUZZACCARINI, Francesco [IT/BE]; 17A, ru XIIII, B-1050 Brussels (BE).</li> <li>(74) Agents: REED, T., David et al.; The Procter &amp; Company, 5299 Spring Grove Avenue, Cincinna 45217 (US).</li> </ul>	69 (US le Vila Gamb	). In
•		

(54) Title: STABLE, AQUEOUS LAUNDRY DETERGENT COMPOSITION HAVING IMPROVED SUSPENSION PROPERTIES

#### (57) Abstract

Heavy duty liquid detergent compositions containing an anionic surfactant component and a quaternary ammonium surfactant are disclosed. The anionic surfactant component comprises, by weight of the composition, from about 5 % to 40 % of alkyl sulfates or alkyl polyethoxylate sulfates. The compositions are structured, provide excellent cleaning of soils, excellent softening, and are capable of suspending particles of up to about 200 microns for at least about one month.

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
ΑŪ	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	1E	Ireland	NZ	New Zealand
BG	Bulgaria	IT	lialy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	
CH	Switzerland	KZ	Kazakhstan	SI	Singapore
CI	Côte d'Ivoire	ü	Liechtenstein	-	Slovenia
CM	Cameroon	LK	Sri Lanka	SK	Slovakia
CN	China	LR	Liberia	SN	Senegal
cs	Czechoslovakia	LT	Lithuania	SZ	Swaziland
CZ	Czech Republic	LU	Luxembourg	TD	Chad
DE	Germany	LV	Latvia	TG	Togo
DK	Denmark	MC	Monaco	TJ_	Tajikistan
EE	Estonia	MD		TT	Trinidad and Tobago
ES	Spain	MG	Republic of Moldova	UA	Ukraine
FI	Finland	ML	Madagascar Mali	UG	Uganda
FR	France		··- <del>-</del> -	US	United States of America
GA	Gabon	MN	Mongolia	UZ	Uzbekistan
	CEDON	MR	Mauritania	VN	Viet Nam

1

STABLE, AQUEOUS LAUNDRY DETERGENT COMPOSITION HAVING IMPROVED SUSPENSION PROPERTIES

#### **TECHNICAL FIELD**

The present invention relates to stable, aqueous heavy duty liquid laundry detergent compositions comprising anionic surfactants and cationic surfactants in a specific ratio to provide exceptional cleaning and softening benefits. Moreover, the detergent compositions herein are structured and have strong suspension properties. The anionic surfactant component comprises alkyl sulfates and alkyl ethoxylated sulfates.

#### **BACKGROUND OF THE INVENTION**

Numerous attempts have been made in the past to formulate laundry detergent compositions which have good cleaning properties and which are capable of suspending particles. However, such liquid detergent compositions present numerous problems to the formulator, including high viscosity at pouring shear rate, insufficient ability to suspend particles, instability during storage, and undesirable appearance.

Attempts to formulate liquid laundry detergent compositions capable of suspending solids in the past have included the use of clays or polymers which act to form a shear thinning composition. While these compositions are capable of suspending particles, many have been found to have poor physical product characteristics, including phase split. Moreover, formulators were limited to a small selection of suitable detergent ingredients in relatively low concentrations.

It has now been found that aqueous, heavy duty liquid detergent compositions containing certain anionic surfactants and quaternary ammonium surfactants provide excellent cleaning performance, softening benefits, and attractive product characteristics, i.e., are structured, phase stable, and have a rheology which allows for the suspension of particles while being easy to pour from the product container.

Without being limited by theory, it is believed that these novel compositions have an internal structure which comprises liquid crystalline surfactant particles, also known as lamellar droplets. These particles are dispersed in the aqueous phase and are capable of suspending solids. Lamellar droplets are known in the art, e.g., H. A. Barnes, "Detergents", in K. Walters (Ed), "Rheometry: Industrial Applications", J. Wiley & Sons, Letchworth 1980. The presence of such surfactant droplets or particles in detergent compositions may be determined by optical means

or by electronic microscope, such as a transmission or scanning electron microscope.

Therefore, it is an object of the invention herein to provide a structured, aqueous heavy duty liquid laundry detergent composition which provides excellent cleaning and softening benefits and a desirable rheology.

#### **BACKGROUND ART**

Cationic surfactants, including quaternary ammonium surfactants, have long been known as useful additives in laundry detergent compositions for the purpose of providing laundered fabrics with a static control benefit (see e.g. U.S. Patent No. 3,951,879, Wixon, issued April 20, 1976, and U.S. Patent No. 3,959,157, Inamorato, issued May 25, 1976, both of which are incorporated herein by reference), a fabric softening benefit (see e.g., U.S. Patent No. 3,607,763, Salmen et al, issued September 21, 1971, U.S. Patent No. 3,644,203, Lamberti et al, issued February 22, 1972, and U.S. Patent No. 3,537,993, Coward et al, issued November 3, 1970, all of which are incorporated herein by reference), or a sanitation benefit (see e.g., U.S. Patent No. 2,742,434, Kopp, issued April 17, 1956, U.S. Patent No. 3,539,520, Cantor et al, issued November 10, 1970, and U.S. Patent No. 3,965,026, Lancz, issued June 22, 1976, all of which are incorporated herein by reference).

#### **SUMMARY OF THE INVENTION**

The present invention encompasses a structured, heavy duty liquid laundry detergent compositions comprising, by weight of the composition:

- a) from about 10% to about 40% of an anionic surfactant component which comprises, by weight of the composition:
  - (i) from about 5% to about 40% of alkyl sulfate or alkyl polyethoxylate sulfates wherein the alkyl group contains from about 10 to about 22 carbon atoms and the polyethoxylate chain contains from 0 to about 15, preferably from 0 to about 5, more preferably from 0 to about 4, ethylene oxide moieties; and
  - (ii) no more than about 5% of fatty acids;
- b) from about 1% to about 10% of a quaternary ammonium surfactant having the formula

$$\begin{bmatrix} R_4 & R_1 \\ N & R_2 \end{bmatrix}^{\mathfrak{S}} \times \mathbb{R}^{\mathfrak{S}}$$

wherein  $R_1$  and  $R_2$  are individually selected from the group consisting of  $C_1$ - $C_4$  alkyl,  $C_1$ - $C_4$  hydroxy alkyl, benzyl, and - $(C_2H_4O)_XH$  where x has a value from about 2 to about 5; X is an anion; and (1)  $R_3$  and  $R_4$  are each a

 $C_6$ - $C_{14}$  alkyl or (2)  $R_3$  is a  $C_6$ - $C_{18}$  alkyl, and  $R_4$  is selected from the group consisting of  $C_1$ - $C_{10}$  alkyl,  $C_1$ - $C_{10}$  hydroxy alkyl, benzyl, and -  $(C_2H_4O)_xH$  where x has a value from 2 to 5;

- c) no more than about 10%, by weight, of solvents or hydrotropes; and
- d) from 0% to about 10% of a suitable electrolyte or acid equivalent thereof; provided that the weight ratio of anionic surfactant to quaternary ammonium surfactant is from about 1.5:1 to about 5:1; and wherein said anionic and quaternary ammonium surfactants form liquid crystalline particles.

The compositions herein have a viscosity at 20 s<sup>-1</sup> shear rate of from about 100 cp to about 4,000 cp, preferably from about 100 cp to about 2,000 cp, more preferably from about 200 cp to about 1,000 cp and are stable upon storage.

All percentages and proportions herein are by weight, and all references cited are hereby incorporated by reference, unless otherwise specifically indicated.

#### **DETAILED DESCRIPTION OF THE INVENTION**

In accordance with the present invention, it has now been found that a stable, aqueous heavy duty liquid detergent composition is surprisingly formed when certain anionic surfactants and a quaternary ammonium surfactants are combined in relative proportions specified hereinafter.

The compositions herein are structured and have a specific rheology. The rheology can be modeled by the following formula:

$$\eta = \eta_O + K \gamma^{(n-1)}$$

where  $\eta$  is the viscosity of the liquid at a given shear rate,  $\eta_0$  is the viscosity at infinite shear rate,  $\gamma$  is the shear rate, n is the shear rate index, and K is the consistency. As used herein, the term "structured" indicates a heavy duty liquid composition having liquid crystalline surfactant particles and an infinite shear viscosity ( $\eta_0$ ) value between 0 and about 3,000cp (centipoise), a shear index (n) value of less than about 0.6, a consistency value, K, of above about 1,000, and a viscosity ( $\eta$ ) measured at  $20^{-1}$  of less than about 10,000cp, preferably less than about 5,000cp. Under low stress levels, a "zero shear" viscosity is above about 100,000cp wherein "zero shear" is meant a shear rate of 0.001 s<sup>-1</sup> or less. The yield value of the compositions herein, obtained by plotting viscosity versus stress, is larger than 0.2Pa. These rheology parameters can be measured with any commercially available rheometer, such as the Carrimed CSL 100 model.

The structured compositions herein are capable of suspending insoluble particles which can be in a solid, liquid, or liquid crystalline phase. By "suspending" is meant the ability to avoid settling or physical separation of particles of up to approximately 200 microns for a period of at least about 30 days.

Relation of Zero Shear Viscosity to Suspension - The capability of a detergent composition to suspend insoluble particles is dependent on the composition's zero shear viscosity. This relationship is modeled by Stoke's Law.

$$v = 2(d_s - d_{fi}) g.r^2 / 9.\eta$$

wherein v is the sedimentation rate of the insoluble;  $d_S$  is the density of insoluble to be suspended;  $d_{fl}$  is the density of fluid to suspend the insoluble; g is gravity; r is radium of the insoluble;  $\eta$  is viscosity.

According to Stoke's Law, the rate of particle sedimentation is inversely proportional to the viscosity, i.e., the higher the viscosity, the more stable the suspension will be. Thus, a high "zero shear" viscosity is preferred, i.e., for this invention a zero shear viscosity of above about 100,000cp, preferably above about 500,000cp, even more preferably above about 1,000,000cp is desired.

The rheology and the suspending ability of these compositions are believed to be caused by the formation, in the specific compositions of this invention, of a space filling network of liquid crystalline surfactant particles (also known in the art as liposomes or vesicles) having a typical size of about 0.1 to about 10 microns. Moreover, the rheological property of the compositions herein is believed to be due in part to the presence in specific amounts of certain electrolytes, including sodium sulfate and citrate. Without being limited by theory, it is believed that the presence of electrolytes acts to control the size of the liquid crystalline surfactant particles. Thus, the structured nature of the compositions herein are affected by the choice of surfactants and by the amount of electrolytes present. In preferred embodiments herein, the compositions will further comprise from 0% to about 10%, more preferably from about 2% to about 6%, even more preferably from about 3% to about 5%, of a suitable electrolyte or acid equivalent thereof. Sodium citrate is a highly preferred electrolyte for use herein.

The compositions herein contain less than about 10%, preferably less than about 7%, more preferably less than about 5%, by weight of solvents and hydrotropes. Without being limited by theory, it is believed that the presence of solvents and hydrotropes can affect the structured versus isotropic nature of the compositions; compositions containing over about 10% solvents and/or hydrotrope lose the ability to remain in a single "phase", i.e., the composition will appear to separate into two or more layers. By "solvent" is meant the commonly used solvents in the detergent industry, including alkyl monoalcohol, di-, and tri-alcohols, ethylene glycol, propylene glycol, propanediol, ethanediol, glycerine, etc. By "hydrotrope" is meant the commonly used hydrotropes in the detergent industry, including short chain surfactants that help solubilize other surfactants. Other

examples of hydrotropes include cumene, xylene, or toluene sulfonate, urea, C<sub>8</sub> or shorter chain alkyl carboxylates, and C<sub>8</sub> or shorter chain alkyl sulfate and ethoxylated sulfates.

The heavy duty liquid laundry detergent compositions herein contain an anionic surfactant component and a quaternary surfactant as essential ingredients.

Anionic Surfactant Component - The detergent compositions herein comprise from about 10% to about 40%, preferably from about 15% to about 25%, by weight of the detergent composition, of an anionic surfactant component. The anionic surfactant component contains alkyl sulfates and/or alkyl polyethoxylate sulfates, and may contain other non-soap anionic surfactants, or mixtures thereof. The anionic surfactant components should not contain more than about 5%, preferably less than about 1%, more preferably substantially free, of fatty acids.

Generally speaking, anionic surfactants useful herein are disclosed in U.S. Patent No. 4,285,841, Barrat et al, issued August 25, 1981, and in U.S. Patent No. 3,919,678, Laughlin et al, issued December 30, 1975, both incorporated herein by reference.

Useful anionic surfactants include the water-soluble salts, particularly the alkali metal, ammonium and alkylolammonium (e.g., monoethanolammonium or triethanolammonium) salts, of organic sulfuric reaction products having in their molecular structure an alkyl group containing from about 10 to about 20 carbon atoms and a sulfonic acid or sulfuric acid ester group. (Included in the term "alkyl" is the alkyl portion of aryl groups.) Examples of this group of synthetic surfactants are the alkyl sulfates, especially those obtained by sulfating the higher alcohols (C8-C18 carbon atoms) such as those produced by reducing the glycerides of tallow or coconut oil.

Other anionic surfactants herein are the water-soluble salts of alkyl phenol ethylene oxide ether sulfates containing from about 1 to about 4 units of ethylene oxide per molecule and from about 8 to about 12 carbon atoms in the alkyl group.

Other useful anionic surfactants herein include the water-soluble salts of esters of  $\alpha$ -sulfonated fatty acids containing from about 6 to 20 carbon atoms in the fatty acid group and from about 1 to 10 carbon atoms in the ester group; water-soluble salts of 2-acyloxy-alkane-1-sulfonic acids containing from about 2 to 9 carbon atoms in the acyl group and from about 9 to about 23 carbon atoms in the alkane moiety; water-soluble salts of olefin sulfonates containing from about 12 to 24 carbon atoms; and  $\beta$ -alkyloxy alkane sulfonates containing from about 1 to 3 carbon atoms in the alkyl group and from about 8 to 20 carbon atoms in the alkane moiety.

Particularly preferred anionic surfactants herein are the alkyl polyethoxylate sulfates of the formula

$$RO(C_2H_4O)_XSO_3^-M^+$$

wherein R is an alkyl chain having from about 10 to about 22 carbon atoms, saturated or unsaturated. M is a cation which makes the compound water-soluble, especially an alkali metal, ammonium or substituted ammonium cation, and x averages from about 1 to about 15.

Preferred alkyl sulfate surfactants are the non-ethoxylated C<sub>12-15</sub> primary and secondary alkyl sulfates. Under cold water washing conditions, i.e., less than abut 65°F (18.3°C), it is preferred that there be a mixture of such ethoxylated and non-ethoxylated alkyl sulfates.

The anionic surfactant component of the present compositions comprises from about 5% to about 40%, preferably from about 7% to about 36%, most preferably from about 10% to about 25%, by weight of the detergent composition, of alkyl sulfates or alkyl polyethoxylate sulfates as described above.

Moreover, the anionic surfactant component herein must comprise no more than about 5% of fatty acids. Most preferably, the detergent compositions herein eontain no fatty acids. These include saturated and/or unsaturated fatty acids obtained from natural sources or synthetically prepared. Examples of fatty acids include capric, lauric, myristic, palmitic, stearic, arachidic, and behenic acid. Other fatty acids include palmitoleic, oleic, linoleic, linolenic, and ricinoleic acid.

#### Quaternary Ammonium Surfactants

The compositions herein also contain from about 1% to about 10%, preferably from about 2% to about 7%, more preferably from about 3% to about 5% by weight of a quaternary ammonium surfactant of the formula:

$$\begin{bmatrix} R_4 & R_1 \\ N & R_2 \end{bmatrix}^{\otimes} X^{\Theta}$$

wherein  $R_1$  and  $R_2$  are individually selected from the group consisting of  $C_1$ - $C_4$  alkyl,  $C_1$ - $C_4$  hydroxy alkyl, benzyl, and - $(C_2H_4O)_xH$  where x has a value from about 2 to about 5; X is an anion; and (1)  $R_3$  and  $R_4$  are each a  $C_6$ - $C_{14}$  alkyl or (2)  $R_3$  is a  $C_6$ - $C_{18}$  alkyl, and  $R_4$  is selected from the group consisting of  $C_1$ - $C_{10}$  alkyl,  $C_1$ - $C_{10}$  hydroxyalkyl, benzyl, and - $(C_2H_4O)_xH$  where x has a value from 2 to 5.

Preferred quaternary ammonium surfactants are the chloride, bromide, and methylsulfate salts. Examples of preferred mono-long chain alkyl quaternary ammonium surfactants are those wherein  $R_1$ ,  $R_2$ , and  $R_4$  are each methyl and  $R_3$  is a  $C_8$ - $C_{16}$  alkyl; or wherein  $R_3$  is  $C_{8-18}$  alkyl and  $R_1$ ,  $R_2$ , and  $R_4$  are selected from

methyl and hydroxyalkyl moieties. Lauryl trimethyl ammonium chloride, myristyl trimethyl ammonium chloride, palmityl trimethyl ammonium chloride, coconut trimethylammonium chloride, coconut trimethylammonium methylsulfate. coconut dimethyl-monohydroxy-ethylammonium chloride, coconut dimethylmonohydroxyethylammonium methylsulfate, steryl dimethyl-monohydroxyethylammonium chloride, stery dimethyl-monohydroxyethylammonium methylsulfate, di- C12-C14 alkyl dimethyl ammonium chloride, and mixtures thereof are particularly preferred. ADOGEN 412™, a lauryl trimethyl ammonium chloride commercially available from Witco, is also preferred. Even more highly preferred are the lauryl trimethyl ammonium chloride and myristyl trimethyl ammonium chloride.

Inventions herein comprise the detergent composition wherein the weight ratio of anionic surfactant component to quaternary ammonium surfactant is from about 1.5:1 to about 5:1, preferably from about 1.5:1 to about 4.5:1, more preferably from about 2:1 to about 3.5:1.

#### **Optional Components**

The compositions of the present invention can also preferably contain up to about 10%, preferably from 0% to about 5%, more preferably from 0% to about 3%, by weight of an ethoxylated nonionic surfactant. These materials are described in U.S. Patent No. 4,285,841, Barrat et al, issued August 25, 1981, incorporated herein by reference. Preferred are the ethoxylated alcohols and ethoxylated alkyl phenols of the formula R(OC<sub>2</sub>H<sub>4</sub>)<sub>n</sub>OH, wherein R is selected from the group consisting of aliphatic hydrocarbon radicals containing from about 8 to about 15 carbon atoms and alkyl phenyl radicals in which the alkyl groups contain from about 8 to about 12 carbon atoms, and the average value of n is from about 5 to about 15. These surfactants are more fully described in U.S. Patent No. 4,284,532, Leikhim et al, issued August 18, 1981, incorporated herein by reference. Particularly preferred are ethoxylated alcohols having an average of from about 10 to abut 15 carbon atoms in the alcohol and an average degree of ethoxylation of from about 6 to about 12 moles of ethylene oxide per mole of alcohol.

The compositions herein also preferably contain up to about 30%, more preferably from about 1% to about 20%, most preferably from about 1% to about 10%, by weight of a non-citrate, non-fatty acid detergent builder material. While all manner of detergent builders known in the art can be used in the present compositions, the type and level of builder should be selected such that the final composition has an initial pH of from about 6.0 to about 11.0, preferably from about 7.0 to about 9.0, at a concentration of about 10% by weight in water at 20°C.

Detergent builders are described in U.S. Patent No. 4,321,165, Smith et al, issued March 23, 1982, incorporated herein by reference. Preferred builders for use in liquid detergents herein are described in U.S. Patent No. 4,284,532, Leikhim et al, issued August 18, 1981, incorporated herein by reference.

Enzymes Enzymes can be included in the formulations herein for a wide variety of fabric laundering purposes, including removal of protein-based, carbohydrate-based, or triglyceride-based stains, for example, and for fabric restoration. The enzymes to be incorporated include proteases, amylases, lipases, and cellulases, as well as mixtures thereof. Other types of enzymes may also be included. They may be of any suitable origin, such as vegetable, animal, bacterial, fungal and yeast origin. However, their choice is governed by several factors such as pH-activity and/or stability optima, thermostability, stability versus active detergents, builders and so on. In this respect bacterial or fungal enzymes are preferred, such as bacterial amylases and proteases, and fungal cellulases.

Enzymes are normally incorporated at levels sufficient to provide up to about 5 mg by weight, more typically about 0.01 mg to about 3 mg, of active enzyme per gram of the composition. Stated otherwise, the compositions herein will typically comprise from about 0.001% to about 5%, preferably 0.01% to 1% by weight of a commercial enzyme preparation. Protease enzymes are usually present in such commercial preparations at levels sufficient to provide from 0.005 to 0.1 Anson units (AU) of activity per gram of composition.

Suitable examples of proteases are the subtilisins which are obtained from particular strains of B. subtilis and B. licheniforms. Another suitable protease is obtained from a strain of Bacillus, having maximum activity throughout the pH range of 8-12, developed and sold by Novo Industries A/S under the registered tradename ESPERASE. The preparation of this enzyme and analogous enzymes is described in British Patent Specification No. 1,243,784 of Novo. Proteolytic enzymes suitable for removing protein-based stains that are commercially available include those sold under the trade names ALCALASE and SAVINASE by Novo Industries A/S (Denmark) and MAXATASE by International Bio-Synthetics, Inc. (The Netherlands). Other proteases include Protease A (see European Patent Application 130,756, published January 9, 1985) and Protease B (see European Patent Application Serial No. 87303761.8, filed April 28, 1987, and European Patent Application 130,756, Bott et al, published January 9, 1985).

Amylases include, for example, α-amylases described in British Patent Specification No. 1,296,839 (Novo), RAPIDASE, International Bio-Synthetics, Inc. and TERMAMYL, Novo Industries.

The cellulase usable in the present invention include both bacterial or fungal cellulase. Preferably, they will have a pH optimum of between 5 and 9.5. Suitable cellulases are disclosed in U.S. Patent 4,435,307, Barbesgoard et al, issued March 6, 1984, which discloses fungal cellulase produced from Humicola insolens and Humicola strain DSM1800 or a cellulase 212-producing fungus belonging to the genus Aeromonas, and cellulase extracted from the hepatopancreas of a marine mollusk (Dolabella Auricula Solander). Suitable cellulases are also disclosed in GB-A-2.075.028; GB-A-2.095.275 and DE-OS-2.247.832. CAREZYME (Novo) is especially useful.

Suitable lipase enzymes for detergent usage include those produced by microorganisms of the Pseudomonas group, such as Pseudomonas stutzeri ATCC 19.154, as disclosed in British Patent 1,372.034. See also lipases in Japanese Patent Application 53,20487, laid open to public inspection on February 24, 1978. This lipase is available from Amano Pharmaceutical Co. Ltd., Nagoya, Japan, under the trade name Lipase P "Amano," hereinafter referred to as "Amano-P." Other commercial lipases include Amano-CES, lipases ex Chromobacter viscosum, e.g. Chromobacter viscosum var. lipolyticum NRRLB 3673, commercially available from Toyo Jozo Co., Tagata, Japan; and further Chromobacter viscosum lipases from U.S. Biochemical Corp., U.S.A. and Diosynth Co., The Netherlands, and lipases ex Pseudomonas gladioli. The LIPOLASE enzyme derived from Humicola lanuginosa and commercially available from Novo (see also EPO 341,947) is a preferred lipase for use herein.

A wide range of enzyme materials and means for their incorporation into synthetic detergent compositions are also disclosed in U.S. Patent 3,553,139, issued January 5, 1971 to McCarty et al. Enzymes are further disclosed in U.S. Patent 4,101,457, Place et al, issued July 18, 1978, and in U.S. Patent 4,507,219, Hughes, issued March 26, 1985, both. Enzyme materials useful for liquid detergent formulations, and their incorporation into such formulations, are disclosed in U.S. Patent 4,261,868, Hora et al, issued April 14, 1981. Enzymes for use in detergents can be stabilized by various techniques. Enzyme stabilization techniques are disclosed and exemplified in U.S. Patent 3,600,319, issued August 17, 1971 to Gedge, et al, and European Patent Application Publication No. 0 199 405, Application No. 86200586.5, published October 29, 1986, Venegas. Enzyme stabilization systems are also described, for example, in U.S. Patent 3,519,570.

The enzymes employed herein may be stabilized by the presence of watersoluble sources of calcium and/or magnesium ions in the finished compositions which provide such ions to the enzymes. (Calcium ions are generally somewhat

more effective than magnesium ions and are preferred herein if only one type of cation is being used.) Additional stability can be provided by the presence of various other art-disclosed stabilizers, especially borate species. See Severson, U.S. 4,537,706. Typical detergents, especially liquids, will comprise from about 1 to about 30, preferably from about 2 to about 20, more preferably from about 5 to about 15, and most preferably from about 8 to about 12, millimoles of calcium ion per liter of finished composition. This can vary somewhat, depending on the amount of enzyme present and its response to the calcium or magnesium ions. The level of calcium or magnesium ions should be selected so that there is always some minimum level available for the enzyme, after allowing for complexation with builders, fatty acids, etc., in the composition. Any water-soluble calcium or magnesium salt can be used as the source of calcium or magnesium ions, including, but not limited to, calcium chloride, calcium sulfate, calcium malate, calcium maleate, calcium hydroxide, calcium formate, and calcium acetate, and the corresponding magnesium salts. A small amount of calcium ion, generally from about 0.05 to about 0.4 millimoles per liter, is often also present in the composition due to calcium in the enzyme slurry and formula water. In solid detergent compositions the formulation may include a sufficient quantity of a water-soluble calcium ion source to provide such amounts in the laundry liquor. In the alternative, natural water hardness may suffice.

It is to be understood that the foregoing levels of calcium and/or magnesium ions are sufficient to provide enzyme stability. More calcium and/or magnesium ions can be added to the compositions to provide an additional measure of grease removal performance. Accordingly, as a general proposition the compositions herein will typically comprise from about 0.05% to about 2% by weight of a water-soluble source of calcium or magnesium ions, or both. The amount can vary, of course, with the amount and type of enzyme employed in the composition.

The compositions herein may also optionally, but preferably, contain various additional stabilizers, especially borate-type stabilizers. Typically, such stabilizers will be used at levels in the compositions from about 0.25% to about 10%, preferably from about 0.5% to about 5%, more preferably from about 0.75% to about 4%, by weight of boric acid or other borate compound capable of forming boric acid in the composition (calculated on the basis of boric acid). Boric acid is preferred, although other compounds such as boric oxide, borax and other alkali metal borates (e.g., sodium ortho-, meta- and pyroborate, and sodium pentaborate) are suitable. Substituted boric acids (e.g., phenylboronic acid, butane boronic acid, and p-bromo phenylboronic acid) can also be used in place of boric acid.

Other preferred components for use in liquid detergents herein are the neutralizing agents, buffering agents, phase regulants, polyacids, suds regulants, opacifiers, dispersants, such as ethoxylated tetraethylene pentaamine, antioxidants, bactericides, dyes, soil release polymers, perfumes, and brighteners described in the U.S. Patent No. 4,285,841. Barrat et al, issued August 25, 1981, incorporated herein by reference. Preferred neutralizing agents for use herein are organic bases, especially triethanolamine and monoethanol amine, which results in better detergency performance than inorganic bases such as sodium and potassium hydroxides.

The compositions herein are suitable for suspending insoluble particles. Particles for suspension include alkyl amine-anionic surfactant ion pair particles, as disclosed in U.S. pat. no. 4,861,502; builders such as zeolites; bleach particles; perfume particles; encapsulated detergent additives; and other known insouble laundry additives.

The following non-limiting examples illustrate the compositions of the present invention. All percentages, parts and ratios used herein are by weight unless otherwise specified.

EXAMPLE I-IV

Liquid detergent compositions were prepared according to the following formulas.

Ingredients	Example I	Examples II
C12-15AE2.5SH	16	16
C45EO7	2.0	0
C12TMAC	5.0	5.0
Citric acid	5.0	5.0
NaOH	~4.5	~4.5
H20	balance	balance
pН	7.0-8	7.0-8
Appearance	Opaque	Opaque
	Suspension	Suspension
Zero Shear Viscosity 10 <sup>6</sup> cp	2.5	8.2
Viscosity (20/s) cp	300	2000

<u>Ingredients</u>	Example III	Examples IV
C12-15AE2.5SH	16	10
C45EO7	2.0	0
C12TMAC	3.0	5.0

Citric acid	5.0	4.0
NaOH	~4.5	~4.0
H20	balance	balance
pН	7.0-8	7.0-8
Appearance	Phase	Suspension
	Separation	
Zero Shear Viscosity 106cp		0.68
Viscosity (20/s) cp		400

The detergent samples are made by the following procedure.

Anionic surfactant paste, C<sub>12-15</sub> alkyl ethoxylate sulfate, is first mixed with alkyl ethoxylate, C<sub>14-15</sub>EO<sub>7</sub> (if present) according to the formula composition, which is followed by the addition of of sodium hydroxide. Citric acid is added immediately after NaOH to bring the pH to about 7.0-8.0 at 10% solution. Lauryl trimethyl ammonium chloride is then added. Immediately after the addition of lauryl trimethyl ammonium chloride, an opaque, lamellar droplet-filled suspension sample is formed. Water and other ingredients are added at the end to complete the formulation.

The compositions of Example I, II, and IV have a viscosity/rheology capable of suspending solids and are stable for more than 30 days.

The composition of Example III undergoes phase split and is undesirable in commercial products.

EXAMPLES V-XI
Liquid detergent compositions were prepared according to the following formulas.

Samples	V	VI	VII	VIII	ĪΙΧ	X	XI
			<del>                                     </del>	1	1		+
C25AE2.5S	<b></b>	20		13.3		20	
C25AS	16			T			<b>-</b>
C45AE2.25S		-	13		16		20
C12TMAC	5	5	4.1	4.2		4	4
C14TMAC					5.0	1	
C45EO7	2	0	1.6	1.6	2.0	0	0
Citric Acid	5	5	6.0	4.2	5.0	2.0	0.5
Borax	1.5	0	1.6	0	2.0	0	0
Propylene glycol	6.4	4.7	3.8	3.7	4.6	4.7	4.7
Ethanol	0	2.2	1.5	1.8	2.3	2.2	2.8
NaOH	Ì		to	pH 7-9	L		
Water	1			o 100%		**********	

Zero Shear Viscosity 10 <sup>6</sup> cp	5.68	0.7	9.9	13	110		n/a
Anionic/Cationi c Ratio	3/1	4/1	3/1	3/1	3/1	5/1	5/1
Viscosity* cp	3000	2400	1700	1440	3300	split	1800

<sup>\*</sup>Viscosity is measure at 20s<sup>-1</sup>.

C25AE2.5S is  $C_{12-15}$  alkyl ethoxylated sulfate with an average degree of ethoxylation of 2.5. C25AS is  $C_{12-15}$  alkyl sulfate. C45AE2.25S is  $C_{14-15}$  alkyl ethoxylated sulfate with an average degree of ethoxylation of 2.25. C12TMAC is  $C_{12}$  trimethyl ammonium chloride. C14TMAC is  $C_{14}$  trimethyl ammonium chloride. C45EO7 is  $C_{14-15}$  alcohol ethoxylate with an average degree of ethoxylation of about 7.

The compositions of Example V-IX and XI have a viscosity/rheology capable of suspending solids and are stable for more than 30 days.

Example X with an anionic/cationic surfactant ratio of 5:1 forms a split phase. However, with routine adjustment of the level of electrolyte and of the chain length of the anionic surfactant, a composition of Example XI with the same anionic/cationic ratio is structured and more phase stable.

EXAMPLE XII

Liquid detergent compositions were prepared according to the following formulas.


ergent compositions were prepared acc	Ording to	o the lone	wing torm
Component	A	<u>B</u>	<u>C</u>
Sodium C <sub>12-15</sub> alkyl	20.0	15.0	25.0
polyethoxylate (2.5) sulfate			
Lauryl trimethyl ammonium	5.0	5.0	5.0
chloride			
C <sub>12-13</sub> alkyl polyethoxylate (9)	2.0	2.0	2.0
C <sub>12</sub> alkyl glucose amide	5.0	5.0	5.0
Citric acid	3.0	3.0	3.0
C <sub>12-14</sub> alkyl fatty acid	2.0	2.0	••
Ethanol	3.7	3.7	3.7
Propanediol	8.0	8.0	8.0
Monoethanolamine	1.1	1.1	1.1
Boric acid	3.5	3.5	3.5
Tetraethylenepentamine	1.2	1.2	1.2
ethoxylated (15-18)			
Sodium cumene sulfonate	3.0	3.0	3.0



Protease enzyme	0.9	0.9	0.9
Lipase enzyme	0.1	0.1	0.1
Cellulase enzyme	0.08		0.08
Sodium hydroxide		to $pH = 8$	<del></del>
Water, perfume and minor ingredients		lance 100	
anionic/cationic surfactant ratio	4/1	3/1	5/1

While the compositions of Example XII have anionic/cationic ratios within the specified ranges of this invention, they are nonetheless outside the scope of this invention because they are isotropic due to the presence of >10% solvents and hydrotropes. The compositions of Example XII does not have a viscosity/rheology capable of suspending solids.

- A structured, heavy duty liquid laundry detergent composition comprising, by weight of the composition:
  - a) from 10% to 40% of an anionic surfactant component which comprises, by weight of the composition:
    - (i) from 5% to 40% of alkyl sulfates or alkyl polyethoxylate sulfates wherein the alkyl group contains from 10 to 22 carbon atoms and the polyethoxylate chain contains from 0 to 15 ethylene oxide moieties; and
    - (ii) no more than 5% of fatty acid surfactants; and
  - b) from 1% to 10% of a quaternary ammonium surfactant having the formula



wherein  $R_1$  and  $R_2$  are individually selected from the group consisting of  $C_1$ - $C_4$  alkyl,  $C_1$ - $C_4$  hydroxy alkyl, benzyl, and - $(C_2H_4O)_XH$  where x has a value from 2 to 5; X is an anion; and (1)  $R_3$  and  $R_4$  are each a  $C_6$ - $C_{14}$  alkyl or (2)  $R_3$  is a  $C_6$ - $C_{18}$  alkyl, and  $R_4$  is selected from the group consisting of  $C_1$ - $C_{10}$  alkyl,  $C_1$ - $C_{10}$  hydroxy alkyl, benzyl, and - $(C_2H_4O)_XH$  where x has a value from 2 to 5;

- c) no more than 10%, by weight, of solvents or hydrotropes; and
- d) from 0% to 10% of a suitable electrolyte or acid equivalent thereof; provided that the weight ratio of anionic surfactant to quaternary ammonium surfactant is from 1.5:1 to 5:1; and wherein said anionic and quaternary ammonium surfactants form liquid crystalline particles.
- 2. The composition of Claim 1 wherein said composition has a viscosity at 20s<sup>-1</sup> shear rate of from 100 cp to 4,000 cp, preferably from 100 cp to 2,000 cp.
- 3. The composition of Claim 1 wherein said composition has a zero shear viscosity above 500,000cp.
- 4. The composition of Claim 1 comprising from 15% to 25% of the anionic surfactant component and less than 7%, by weight of solvents or hydrotropes.
- 5. The composition of Claim 4 wherein the anionic surfactant component of the anionic surfactant comprises from 7% to 36%, preferably from 10% to 25%, alkyl ethoxylated sulfates.

- 6. The composition of Claim 5 comprising from 3% to 5% of the quaternary ammonium surfactant.
- 7. The composition of Claim 1 wherein the quaternary ammonium fabricsoftening agent is selected from the group consisting of lauryl trimethyl ammonium chloride, myristyl trimethyl ammonium chloride, palmityl trimethyl ammonium chloride, coconut trimethyl ammonium chloride, coconut trimethyl ammonium methylsulfate, coconut dimethyl-monohydroxyethylammonium chloride, coconut dimethyl-monohydroxyethylammonium methylsulfate, steryl dimethyl-monohydroxyethylammonium chloride, dimethyl-monohydroxyethylammonium steryl methylsulfate, di- C12-C14 alkyl dimethyl ammonium chloride, and mixtures thereof.
- 8. The composition of Claim 7 comprising from 3% to 5% of lauryl trimethyl ammonium chloride.
- 9. The composition of Claim 7 comprising from 3% to 5% of myristyl trimethyl ammonium chloride.
- 10. The composition of Claim 1 wherein the weight ratio of anionic surfactant component to quaternary ammonium surfactant is from 2:1 to 3.5:1.
- 11. The composition of Claim 1 further comprising up to 10% of an ethoxylated nonionic surfactant.
- 12. The composition of Claim 1 further comprising from 1% to 20% of a non-citrate, non-fatty acid detergent builder material.
- 13. The composition of Claim 1 further comprising an enzyme selected from the group consisting of proteases, amylases, lipases, cellulases and mixtures thereof at a level sufficient to provide from 0.01 mg to 3 mg of active enzyme per gram of the composition.

WO 97/12019 PCT/US96/15522

17

14. The composition of Claim 1 wherein said composition is capable of suspending particles of up to approximately 200 microns for a period of at least one month.

#### INTERNATIONAL SEARCH REPORT

Internal ul Application No PCT/US 96/15522

			101/05 70/10566
A. CLAS IPC 6	SIFICATION OF SUBJECT MATTER C11D1/65 C11D1/86 C11D1	7/00	
According	to International Patent Classification (IPC) or to both national of	lossification and IPC	
B. FIELD	S SEARCHED		
IPC 6	documentation searched (classification system followed by class C11D	dicanon symbols)	
Document	anon searched other than minimum documentation to the extent	that such documents are includ	ed in the fields searched
Electronic	data base consulted during the international search (name of data	s base and, where practical, see	urch terms used)
C. DOCUN	MENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	ne relevant passages	Relevant to claim No.
X	US,A,4 235 759 (JOHNA NOBUO ET November 1980 see examples 3-9,12-14,17-19; c		1-14
X	GB,A,2 185 992 (COLGATE PALMOLI August 1987 see page 2, line 31 - page 3, l claim 1; example 1		1-14
A	EP,A,O 008 142 (PROCTER & GAMBL; PROCTER & GAMBLE (BE)) 20 Febrasee page 11, line 30 - line 34		12,13
A	EP,A,0 095 205 (PROCTER & GAMBLE November 1983 see page 9, line 10 - page 10,		12,13
		-/	
X Furth	er documents are listed in the continuation of box C.	Patent family memb	pers are listed in annex.
•	genes of cred documents:  In defining the general state of the art which is not	or priority data and not	d after the international filling date in conflict with the application but principle or theory underlying the
conside	red to be of particular relevance ocument but published on or after the international	"X" document of particular i	relevance; the claimed invention
which ii	nt which may throw doubts on priority claim(s) or streed to establish the publication date of another or other special reason (as specified)	"Y" document of particular i	p when the document is taken alone relevance; the claimed invention involve an inventive step when the
O, qoeranci	nt referring to an oral disclosure, use, exhibition or eans	document is combined to	with one or more other such docu- n being obvious to a person stalled
later tha	at published prior to the international filing date but in the priority date claimed	*& document member of the	
	ctual completion of the international search		·
	January 1997 Duling oddress of the ISA	0 3. [	<i>L.</i> 97
-carre carra file	European Patent Office, P.B. 5918 Patentiaan 2 NL - 2280 HV Riptonk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,	Ainscow. J	

### INTERNATIONAL SEARCH REPORT

Interno at Application No PCT/US 96/15522

		PCT/US 9	0/13322
	auon) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.
A	EP,A,O 085 448 (PROCTER & GAMBLE ;PROCTER & GAMBLE LTD (GB)) 10 August 1983		
۹ ا	EP,A,O 456 569 (COLGATE PALMOLIVE CO) 13 November 1991		united and the state of the sta
	· · · · · · · · · · · · · · · · · · ·		
	·		

1

#### INTERNATIONAL SEARCH REPORT

.ormation on patent family members

Intern: al Application No PCT/US 96/15522

Patent document cited in search report	Publication date		nt family nber(s)	Publication date
US-A-4235759	25-11-80	JP-C-	1543570	15-02-90
		JP-A-	54159416	17-12-79
		JP-B-	63037158	22-07-88
GB-A-2185992	05-08-87	AT-A,B	17687	15-11-93
	00 00 07	AU-B-	595851	12-04-90
		AU-A-	6805387	06-08-87
		BE-A-	1002958	08-10-91
		CH-A-	671963	13-10-89
		DE-A-	3702287	06-08-87
		EG-A-	18097	30-08-92
		FR-A-	2593516	31-07-87
		HK-A-	97693	30-09 <b>-</b> 93
		JP-B-	7113119	06-12-95
		JP-A-	62197496	01-09-87
		KR-B-	9503426	12-04-95
		NL-A-	8700231	17-08-87
		SE-A-	8700324	31-07-87
EP-A-0008142	20-02-80	CA-A-	1133407	12-10-82
		US-A-	4302364	24-11-81
EP-A-0095205	30-11-83	AU-B-	559791	19-03-87
E. 7. 0030E05	30 11 03	AU-A-	1488883	01-12-83
		CA-A-	1208519	29-07-86
•		JP-C-	1785137	31-08-93
		JP-B-	4077038	07-12-92
		JP-A-	59025894	09-02-84
		US-A-	4561998	31-12-85
EP-A-0085448	10-08-83	NONE		
 EP-A-0456569	13-11-91	AU-A-	7633491	14-11-91
LI A-V4JUJUJ	17-11-31	CA-A-	2041716	09-11-91
		US-A-	5290475	01-03-94